Sendzimir 20 High Cold Rolling Mill

Manufactured by DMS (under license of Sendzimir Inc.)



General Specifications

MANUFACTURER:

DMS (France)

COMMISSIONING DATE:

1992

MODEL:

ZR22BBS52

PRODUCTION CAPACITY:

250,000t

INPUT MAX:

0.0250"x 52"

OUTPUT MAX:

0.009" x 52"

ENTRY MATERIAL:

High / Low Carbon Steel / Stainless Steel

ENTRY COIL:

52" Wide (1320mm)

0.25" (6.3mm) Thickness

35.8" to 72" O.D. (910mm to 1830mm)

24" I.D. (610mm)

EXIT COIL:

23.6" to 52" Wide (600mm to 1321mm)

0.009" Thickness (0.22mm)

35.8" to 72" O.D. (910mm to 1830mm)

24" I.D. (610mm)

COIL WEIGHT:

20,000Kgs

LINE SPEED:

2500fpm (762mpm)

TENSION:

40,000Kg Max.

DIRECTION OF TRAVEL:

Right to left seen from Operator's side.

BACKUP BEARINGS:

11.750" / 11.810" (298mm / 300mm)

SECOND INTERMEDIATE ROLLS:

6.875" / 7.200" (175mm / 183mm)

FIRST INTERMEDIATE ROLLS:

3.900" / 4.200" (99mm / 107mm)

WORK ROLLS:

2.900" / 3.400" (74mm / 86mm)

ROLL OPENING:

0.345" MAX (8.76mm)

HOUSING TYPE:

CLOSED TOP

MAIN DRIVE MOTOR:

4000HP DC (3000Kw)

(2 x 2000HP) (2 x 1500Kw)

395 / 1000 RPM - 730 v

PAYOFF REEL:

24" DIA MANDREL (610mm) 160HP MOTOR DC (120Kw)

770 / 2300 RPM - 400 v

ENTRY REEL:

24" DIA MANDREL (610mm) 4000HP MOTOR DC (2 x 2000HP)

(2 x 1500Kw)

395 / 1000RPM – 730v

EXIT REEL:

24" DIA MANDREL (610mm)

4000HP MOTOR DC (2 x 2000HP)

(2 x 1500Kw)

395 / 1000RPM – 730v

INCLUDED:


Electrical Drives, 2 Gamma Gauges, 2 Rotary Shears, Automatic Gauge Control, Hydraulic side guides, Lubrication systems, Full Drawings, Operating Spares.

MAIN MECHANICAL COMPONENTS:

Payoff, 20 high cage, 2 mandrels, 2 gamma gages, 2 rotary shears, Automatic gage control, Hydraulic side guides, Includes gear box, hydraulics and lubrification systems

TDI REFERENCE NUMBER

4416





PAYOFF REEL: 24" DIA MANDREL (610mm) 160HP MOTOR DC (120Kw) 770 / 2300RPM – 400v

MATERIAL FLATTENER





CARRYOVER TABLE (VERTICAL POSITION)

TENSION REEL #1 W/ OUTBOARD BEARING SUPPORT
24" DIA MANDREL (610mm)
4000HP MOTOR DC (2 x 2000HP)
(2 x 1500Kw)
395 / 1000RPM – 730v





CLOSE UP OF OUTBOARD BEARING SUPPORT


ENTRY GAMMA GAUGE, ROTARY SHEAR, AUTOMATIC GAUGE CONTROL, HYDRAULIC SIDE GUIDES





20 HIGH CLUSTER MILL HOUSING

DELIVERY GAMMA GAUGE, ROTARY SHEAR, AUTOMATIC GAUGE CONTROL, HYDRAULIC SIDE GUIDES



TENSION REEL #2 W/ OUTBOARD BEARING SUPPORT
24" DIA MANDREL (610mm)
4000HP MOTOR DC (2 x 2000HP)
(2 x 1500Kw)
395 / 1000RPM – 730v



VIEW FROM END OF MILL





EXHAUST SYSTEMS AND DUCT WORK

MILL MOTOR ROOM



PANORAMIC VIEW OF MILL

