

EQUIPMENT SPECIFICATIONS

SHEARS

.040" - .500" X 74" MONARCH-STAMCO HYDRAULIC SHEAR
TDI REFERENCE NUMBER: 64303

MANUFACTURER: Monarch-Stamco
AGE: 2000
QUANTITY: 1.00

GENERAL SPECIFICATIONS:

SHEAR MANUFACTURER:	<u>Stamco</u>
SHEAR DESIGN:	<u>Cold</u>
MATERIAL PROCESSED:	<u>Steel</u>
CAPACITY:	
WIDTH MINIMUM (INCHES):	<u>24 Inches (609.600 mm)</u>
WIDTH MAXIMUM (INCHES):	<u>74 Inches (1,879.600 mm)</u>
THICKNESS MINIMUM (INCHES):	<u>0.040 Inches (1.016 mm)</u>
THICKNESS MAXIMUM (INCHES):	<u>0.500 Inches (12.700 mm)</u>
OPERATING SPEED (FPM):	<u>150/300 Fpm</u>
KNIFE:	
WIDTH (INCHES):	<u>78 Inches (1,981.200 mm)</u>
OPERATION:	<u>Hydraulic Cylinder</u>
HYDRAULIC CYLINDER BORE (INCHES):	<u>10 Inches (254.000 mm)</u>
HYDRAULIC CYLINDER STROKE (INCHES):	<u>5 Inches (127.000 mm)</u>
MATERIAL TRAVEL:	<u>Left to Right</u>
PASS LINE (INCHES):	<u>60 Inches (1,524.000 mm)</u>
DRIVE MOTOR:	
HORSEPOWER:	<u>50 HP (37.300 kw)</u>
CURRENT:	<u>AC</u>

PREVIOUS USE:

CTL Application

FEATURES:

hydraulic - 460V/3ph/60hz

APPROXIMATE OVERALL DIMENSIONS (INCHES):

LENGTH (INCHES):

120 Inches (3,048.000 mm)

WIDTH (INCHES):

84 Inches (2,133.600 mm)

HEIGHT (INCHES):

144-sembled Inches

COMMENTS:

Shear is removed from foundation, Inclusive of Hydraulic System & Available Spare Parts 3 hyd _____ cylinder 2@10" bore, 1@8" bore, 5" stroke, 5.5" Rod Dia. Push/Pull 3000 PSI _____